

AD-A069 140

TRACOR INC AUSTIN TEX
AN/SQS-26(BX) CODED PROCESSOR AND DISPLAY PERFORMANCE.(U)
NOV 67 D W DUDERSTADT
TRACOR-67-953-U


F/G 17/1

UNCLASSIFIED

1 OF 1
AD
A069 140

NOBSR-95149

NL



END
DATE
FILMED

7-79
DDC

5: MOST PROJECT
LEVEL II

1
NW

Contract NObsr 95149 MOD 4
Project Serial SS041 001
Tasks 8100, 8156, 8193
TRACOR Project 002 019 14
Document Number 67-953-U

002683

TECHNICAL MEMORANDUM

AN/SQS-26(BX) CODED PROCESSOR
AND DISPLAY PERFORMANCE (U)

Submitted to:

Commander,
Naval Ship Systems Command
Department of the Navy
Washington, D. C. 20360
Attention: PMS-87

30 November 1967

AD A069140

DDC FILE COPY

DDC
RECEIVED
MAY 30 1979
D

TRACOR

6500 Tracor Lane, Austin, Texas 78721, AC 512/926-2800

Gp. 9

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited



6500 TRACOR LANE, AUSTIN, TEXAS 78721

Contract NObsr 95149 MOD 4
Project Serial SS041 001
Tasks 8100, 8156, 8193
TRACOR Project 002 019 14
Document Number 67-953-U

(14)

TRACOR

(15)

NObsr-95149

(9)

TECHNICAL MEMO ~~NUMBER~~ 1 Mon-30 Nov

(6)

AN/SQS-26(BX) CODED PROCESSOR
AND DISPLAY PERFORMANCE.

(12) 19p.

Submitted to:

Commander,
Naval Ship Systems Command
Department of the Navy
Washington, D. C. 20360
Attention: PMS-87

ACCESSION to	
DTIC	White Section <input checked="" type="checkbox"/>
DDC	Ref Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
Per Hq. on file	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. and/or SPECIAL
A	

Approved

G. T. Kemp
G. T. Kemp
Program Manager

(11)

30 November 1967

DDC
RECEIVED
MAY 30 1979
D

Prepared

(10) *D. W. Duderstadt*
Douglas W. Duderstadt
Project Director

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

671207-0104

352 700



TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
	LIST OF FIGURES	iii
1.	SUMMARY	1
2.	BACKGROUND	1
3.	CODED PROCESSOR GAIN	2
4.	EFFECTIVE LOSS BETWEEN PROCESSOR OUTPUT AND DISPLAY	3
5.	CONCLUSIONS AND RECOMMENDATIONS	9

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	COMPARISON OF COMPUTER SIMULATED AND AN/SQS-26 (BX) CLIPPED CORRELATOR PROCESSORS ON AN OUTPUT SIGNAL-TO-NOISE RATIO BASIS	4
2.	OUTPUT SIGNAL-TO-NOISE RATIO AS A FUNCTION OF INPUT SIGNAL-TO-NOISE RATIO IN A 100 HZ AND A 500 HZ NOISE BAND. CLIPPED REPLICA CORRELATOR USING A 1/2 SECOND, 100 HZ BANDWIDTH LINEAR FM SLIDE SIGNAL	5
3.	REQUIRED INPUT SIGNAL-TO-NOISE RATIO FOR 0.5 PROBABILITY OF DETECTION VS RATE OF EXCEEDING THRESHOLD AT THE OUTPUT OF A CLIPPED CORRELATOR OPERATING ON 100 HZ FM SLIDE SIGNALS IN RECTANGULAR NOISE	7
4.	CLIPPED REPLICA CORRELATOR OUTPUT SIGNALS SPACED ONE SECOND APART	8
5.	MEASURED PROBABILITY THAT THE OUTPUT SIGNAL-TO-NOISE RATIO OF THE CLIPPED REPLICA CORRELATOR EXCEEDS THE ABSCISSA FOR THE INDICATED INPUT SIGNAL-TO-NOISE RATIO	10
6.	CLIPPED REPLICA CORRELATOR OUTPUT FOR NOISE ALONE	11



1. SUMMARY

This document reports the analysis of sea test data recorded from the AN/SQS-26(BX) sonar system to check the performance of the coded processor.

The analysis of data recorded by USL aboard the USS WAINWRIGHT (DLG-28) shows that the gain of the clipped correlator coded processor is in accordance with theory. A comparison of expected performance criteria with signal detectability measurements made by USL during the sea tests shows a 2.5 dB loss in effective (S/N) between the coded processor output and the display output.

2. BACKGROUND

This work is an outgrowth of the effort to pinpoint the causes of significant losses in performance reported by USL during sea tests conducted aboard the USS WAINWRIGHT (DLG-28) from 28 May 1966 to 23 June 1966. An examination of this sea test data during the period 1 July 1966 to 4 October 1966 yielded no clear cut determination of any specific system failure that could have caused the observed loss in performance at sea [1].

On 5 October 1966 a meeting of USL, EDO, TRACOR, and PMS-87 personnel was held at the EDO plant in New York. At that time it was concluded that further analysis of the sea test data on hand would not yield a solution to the problem, and USL was directed to prepare a plan for another test. USL presented this plan to PMS-87 on 26 January 1967. TRACOR's subsequent work has been concerned with the analysis of data recorded aboard the USS WAINWRIGHT (DLG-28) in accordance with this plan.

USL carried out an extensive test program aboard the USS WAINWRIGHT (DLG-28) during the period 13 March 1967 through 1 May 1967. USL reported the results of this test program to PMS-87 on 26 May 1967 and to a meeting of EDO, USL, TRACOR, and PMS-87 representatives on 2 June 1967.



The USL results cited two factors which may have contributed to the loss in performance observed in June 1966. These were as follows:

1. A voltage controlled oscillator in the sonar system test set had drifted as much as 40 Hz during some of the test sequences. Since this oscillator controls the frequency of the test set signal, it could have caused the observation of an apparent performance loss when the test set was being used to measure the minimum detectable signal level (MDL) during the tests.

2. Excessive noise was observed in the video scanner (multiplexer) circuitry between the twelve channels of coded processor output and the scan converter prior to the display. This noise may be a contributing factor in losses between the processor output and the display observed by USL during the 1967 sea tests.

The purpose of this report is to show results validating the performance gain of the coded processor and to place an effective "dB" value on the loss between the processor output and the display output.

3. CODED PROCESSOR GAIN

The test equipment producing the data recorded from the AN/SQS-26(BX) system was designed to test the system performance under realistic conditions aboard ship. The tests, consisting of variations of synthetic signals and noise injected into the system, were made at dockside and at sea.

To check the performance of the coded processor, TRACOR compared the output of a computer simulated processor with that of the hardware processor for the same sets of input data. The signals and noise used for the simulation were taken from the input to the coded processor, as recorded on the sea test tapes.



Figure 1 shows a plot of computer simulated correlator output signal-to-noise ratio (S/N) vs hardware correlator output (S/N) for the same data. This figure shows the measurements falling about a 45° line, indicating equal average gains in (S/N) through the processor, except for random fluctuations.

Figure 2 shows a comparison of measured processing gains between computer simulated, hardware, and theoretical processors. These are in agreement within 0.5 dB for the input (S/N) range of interest here. Output (S/N) is plotted as a function of input (S/N) measured in a 500 Hz noise band in order to make numerical comparisons with similar data presented by USL. Input (S/N) relative to a 100 Hz band is also shown for reference and comparison with data presented in Section 4.

4. EFFECTIVE LOSS BETWEEN PROCESSOR OUTPUT AND DISPLAY

The measurements conducted by USL observers on board the USS WAINWRIGHT (DLG-28) established a 50% probability of detection for an input (S/N) of -11.5 dB as measured in a 500 Hz noise band at the input to the Automatic Gain Control (AGC). This corresponds to an average +15.5 dB output (S/N) for the hardware coded processor. The observers were alerted, in that they knew the expected location of the signal and knew that the signal had been injected into the system on each sweep.

The USL observers noted that the signal detectability was better on a makeshift storage oscilloscope display monitoring the coded processor output than on the A-scan sonar display, under the same signal conditions. The observers reported that signals at an input (S/N) of -11.5 dB could be detected about 90% of the time on the storage scope while being detected only 50% of the time on the display. USL reported potential causes and observations relating to this loss at the meeting between USL, TRACOR, EDO, and PMS-87 representatives at USL 2 June 1967.




Figure 1 COMPARISON OF COMPUTER SIMULATED AND AN/SQS-26(BX) CLIPPED CORRELATOR PROCESSORS ON AN OUTPUT SIGNAL-TO-NOISE RATIO BASIS




Figure 2 OUTPUT SIGNAL-TO-NOISE RATIO AS A FUNCTION OF INPUT
SIGNAL-TO-NOISE RATIO IN A 100 Hz AND A 500 Hz NOISE BAND

To place a "dB" value on this reported loss, consider the following:

(a) For signals injected at -11.5 dB in a 500 Hz band, the hardware processor output (S/N) is 15.5 dB (See Figure 2). In the sea tests conducted by USL, this output was observed to correspond to the effective display threshold for 50% probability of detection. For a 100 Hz bandwidth, which will be used in the remainder of the discussion, the corresponding input (S/N) is -4.5 dB.

(b) Figure 3 shows the required input signal-to-noise ratio for 0.5 probability of detection as a function of rate of exceeding threshold for the processor under consideration here [2]. As shown in Fig. 3, an input (S/N) of -4.5 dB in a 100 Hz noise band corresponds to the threshold at which the threshold crossing rate is $5 \times 10^{-3} \text{sec}^{-1}$, or an average of one crossing every 200 seconds. Making the conservative assumption that a threshold crossing rate of one every 10 seconds is reasonable for a single sweep, it can be seen in Fig. 3 that the operating threshold should be that corresponding to an input (S/N) of -6.5 dB, which would give an output (S/N) of +13 dB. For greater crossing rates, the operating threshold would be lowered even more, so that it can be concluded that at least 2.5 dB are lost between the coded processor output and the display output. The AN/SQS-26 display should, therefore, be able to operate at an effective threshold of 13 dB referred to the coded processor output.

To illustrate the significance of this 2.5 dB loss, Fig. 4 shows a sequence of signals one second apart with the amplitude plotted vertically on a linear scale. These clipped correlator outputs were prepared using $\frac{1}{2}$ second FM slide signals added at one second intervals into 100 Hz bandwidth noise to yield average output signal-to-noise ratios of 15.5 dB and 13 dB. In traces A and B, note the change in ability to detect the 15.5 dB signals over the 13 dB signals without reference to threshold. Traces C and D

- 2 -





Figure 3 REQUIRED INPUT SIGNAL-TO-NOISE RATIO FOR 0.5 PROBABILITY OF DETECTION vs RATE OF EXCEEDING THRESHOLD AT THE OUTPUT OF A CLIPPED CORRELATOR OPERATING ON 100 CPS FM SLIDE SIGNALS IN RECTANGULAR NOISE

Figure 4 CLIPPED REPLICA CORRELATOR-OUTPUT SIGNALS
SPACED 1 SECOND APART

100 Hz Bandwidth, 1/2 Second FM Slide Signals
Time Scale: 10 mm = 1 Second





from the same sequences of data have 15.5 and 13 dB thresholds marked. In trace C, significantly more signals can be detected without an excessive increase in false alarm rate by changing the threshold from 15.5 to 13 dB.

Figure 5 shows the measured probability that the clipped replica correlator output will exceed a given threshold for average input signal-to-noise ratios as shown [3]. This curve may be used to estimate the expected spread in output signal-to-noise ratio for a given input signal-to-noise ratio. For example, 90% of signals with an average input (S/N) of -3 dB will lie between 14 dB and 19 dB. The curve also may be used to determine the change in probability of detection for a given average input (S/N) as the detection threshold is changed. For the case considered in the preceding paragraph a sequence of 100 signals was added to the noise to yield 15.5 dB average output (S/N). Fifty-two of these signals exceeded a 15.5 dB threshold, 87 exceeded a 13 dB threshold. This is in close agreement with the same change indicated on the curve for -4.5 dB input (S/N).

To further support the assumption that a 13 dB operating threshold would not result in an excessive false alarm rate, consider Fig. 6. This figure shows 100 seconds of clipped correlator output using noise alone as input. The noise never crosses the 15.5 dB threshold, and it crosses the 13 dB threshold only three times. A 10 dB threshold is shown to illustrate how quickly the threshold crossing rate changes to an unacceptable value as the threshold is lowered.

5. CONCLUSIONS AND RECOMMENDATIONS

From the data presented in Sections 3 and 4 it is concluded that the coded processor is performing properly and that 2.5 dB is lost between the processor output and the display output for the AN/SQS-26(BX) system aboard the USS WAINWRIGHT. The causes of this loss, except for the excessive noise in the video scanner





Fig. 5 - MEASURED PROBABILITY THAT THE OUTPUT SIGNAL-TO-NOISE RATIO OF THE CLIPPED CORRELATOR EXCEEDS THE ABSCISSA FOR THE INDICATED INPUT SIGNAL-TO-NOISE RATIO



11

100 Hz Bandwidth; 1/2 Second FM Slide Replica

Time Scale: 2.5 mm = 1 Second

Total Length of Trace = 100 Seconds

Output Signal-to-Noise Ratio Thresholds as Marked

Figure 6 CLIPPED REPLICAS CORRELATOR OUTPUT FOR NOISE ALONE



6500 TRACOR LANE, AUSTIN, TEXAS 78721

circuitry noted by USL, are unknown. No data are available on the recorded tapes to investigate problems in the display subsystem. If this problem appears consistently in all AN/SQS-26(BX) systems, it is a serious one, warranting further investigation to determine if corrective action can be taken without extensive hardware modifications.

Due to the lack of evidence to support any requirements for further investigation and analysis of the 1967 sea test data, this task is considered to be completed, and it is recommended that further efforts to describe and verify expected signal processor and display characteristics, if required, be continued as a part of the overall display and signal processing work programs being carried out by TRACOR.



REFERENCES

1. Butler, B. and Duderstadt, W. ANALYSIS OF AN/SQS-26(BX) SONAR DATA FROM USS WAINWRIGHT (DLG-28) SEA TEST OF 28 MAY to 23 JUNE, 1966 - Technical Note. October 4, 1966. TRACOR Document Number 66-477-U.
2. ANALYSIS OF SIGNAL PROCESSING AND RELATED TOPICS PERTAINING TO THE AN/SQS-26 SONAR EQUIPMENT (U) - A Summary Report, III. TRACOR Document Number 65-336-C. October 15, 1965.
3. ANALYSIS OF SIGNAL PROCESSING AND RELATED TOPICS PERTAINING TO THE AN/SQS-26 SONAR EQUIPMENT (U) A SUMMARY REPORT, II. TRACOR Document Number 64-290-C. 16 October 1964.

UNCLASSIFIED

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION
TRACOR, Inc. 6500 Tracor Lane, Austin, Texas 78721		Unclassified
		2b. GROUP
		N.A.
3. REPORT TITLE		
AN/SQS-26(BX) CODED PROCESSOR AND DISPLAY PERFORMANCE(U)		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
Technical Memorandum, 1 March 1967 to 30 November 1967		
5. AUTHOR(S) (Last name, first name, initial)		
Duderstadt, Douglas W.		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
30 November 1967	16	3
8a. CONTRACT OR GRANT NO.	9a. ORIGINATOR'S REPORT NUMBER(S)	
NObsr-95149, MOD 4, b. PROJECT NO. SS 041-001 c. Task 8100, 8156, 8193 d.	67-953-U	
	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
	None	
10. AVAILABILITY/LIMITATION NOTICES		
<div style="border: 1px solid black; padding: 5px; text-align: center;"> DISTRIBUTION STATEMENT A Approved for public release; Distribution Unlimited </div>		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY
None		Naval Ship Systems Command Department of the Navy Washington, D. C. 20360
13. ABSTRACT		
<p>From the AN/SQS-26(BX) sonar system analysis of data recorded aboard the USS WAINWRIGHT (DLG-28) shows that the coded processor system performs in accordance with theory. A comparison of signal detectability measurements with expected performance criteria shows a 2.5 dB loss in effective signal-to-noise ratio between the processor output and the display output.</p>		

DD FORM 1 JAN 64 1473

UNCLASSIFIED

Security Classification

14.

KEY WORDS

AN/SQS-26 (BX) Sonar System
 AN/SQS-26 (BX) Coded Processor Tests
 Clipped Replica Correlator

LINK A

LINK B

LINK C

ROLE

WT

ROLE

WT

ROLE

WT

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification